

NeO - Laser



54815648 465464

**Robustez, Fiabilidad y
Diseño a bajo coste**

Scanner Laser

- Pulsador
- Indicador Led y Audio
- Larga distancia
- 120 Scaneos por Seg.



vivapos®



Códigos de Producto

006016-02.04.05.01 - SCANNER LASER NEO SL-200 KB
 006016-02.04.05.03 - SCANNER LASER NEO SL-200 USB



Especificaciones

	SL-200
Light source	Visible Laser Diode 650nm
Depth of scan field	10 – 220 mm (UPC/EAN 100%)
Scanning angle	42°
Scan speed	120scans/sec
Scan pattern	Single-line Mode
Indicator(LED)	Blue LED
Beeper operation	adjustable frequency and tone
System interfaces	KB, RS-232,USB
PHYSICAL	
Height	104.90 mm
Thickness	152.3 mm
Width	64.4 mm
Weigh	120 g (Cable excluded)
Cable	2m(straight)
POWER	
Input voltage	5 VDC ±5%
Operating current	100 mA typical
REGULATORY	
EMC	CE EN55022B; FCC Part 15 Class B, VCCI, BSMI, Rohs
ENVIRONMENTAL	
Operating temperature	0°C 50°C (32°F 122°F)
Storage temperature	-20°C 60°C (-4°F 140°F)
Humidity	20% 85% RH (non-condensing)
Light level	Max. 20,000 Lux (fluorescence)
Shock	Designed to withstand 1.5m drop onto concrete
DECODING CAPABILITY	
Decode capability	UPC/EAN/JAN, UPC/EAN with supplementary, JAN 8 & JAN 13, ISBN/ISSN, Japanese Bookland EAN, Code 39, Code 39 with full ASCII, Codabar (NM7), Code 128, Code 128 with full ASCII, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, Code 32
Patulous code	Industrial 2 of 5, Standard 2 of 5, Discrete 2 of 5, Matrix 2 of 5, Code 11, UPC/EAN RSS, RSS variants

