

Thor - Laser



54815648 4654646

**Omnidireccional, Robusto,
Fiable y de bajo coste**

Scanner Laser

- 20 Líneas Omnidireccional
- Pulsador
- Indicador Led y Audio
- 1400 Scaneos por Seg.





Códigos de Producto

006018-02.04.01.01 - SCANNER LASER THOR SM-700 KB

006018-02.04.01.03 - SCANNER LASER THOR SM-700 USB



vivapos®

Especificaciones

	SL-700
Light source	650nm laser
Depth of scan field	0 – 220 mm
scan lines	20
Scan speed	1400 lines/sec;74 scan lines per second (single-line mode)
Minimum Bar Width	5.000 @ PCS 90%
Print contrast	≥ 35%
scan mode	omnidirectional scan (5 positions with 4 lines for each)
Indicators (LED)	Blue LED
System interfaces	KB, RS-232,USB
PHYSICAL	
Height	110.9mm
Thickness	168.5 mm
Width	70.0mm
Weigh	200 g (Cable excluded)
Cable	2m(straight)
POWER	
Input voltage	5 VDC ±5%
Operating current	200 mA typical
REGULATORY	
EMC	CDRH Class Ila, IEC 60825 Class 2 EMC CE EN55022B; FCC Part 15 Class B, VCCI, BSMI, Rohs
ENVIRONMENTAL	
Operating temperature	0°C 40°C (32°F – 104°F)
Storage temperature	-20°C 60°C (-4°F – 140°F)
Humidity	5% 90% RH (non-condensing)
Light level	Max. 4842 Lux (fluorescence)
DECODING CAPABILITY	
Decode capability	UPC/EAN/JAN, UPC/EAN with supplementary, JAN 8 & JAN 13, ISBN/ISSN, Japanese Bookland EAN, Code 39, Code 39 with full ASCII, Codabar (NM7),Code 128, Code 128 with full ASCII, Code 93,Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code,Code 32
Patulous code	Industrial 2 of 5, Standard 2 of 5, Discrete 2 of 5, Matrix 2 of 5, Code 11, UPC/EAN RSS, RSS variants

